



थासाङ गाउँपालिका

गाउँ कार्यपालिकाको कार्यालय



कोबाङ, मुस्ताङ
गण्डकी प्रदेश, नेपाल

पत्र संख्या: २०८२/०८३

सूचना नं.: ६२

वि.सं.: २०८२/०९/०२

ने.सं.: ११४६ वी.ला.गा. १३

प्रचलित बजारभाउ पेश गर्ने सम्बन्धमा।

प्रस्तुत विषयमा थासाङ गाउँपालिका अन्तर्गत लेते र टुकुचे गाउँमा सिसिभिभी जडान गर्नुपर्ने भएको हुँदा यसैसाथ संलग्न स्पेशिफिकेशन अनुरूपका सामग्रीहरूको दररेट सूचनाको मितिले ७ दिनभित्र पेश गर्नुहुन सम्बन्धित सबैमा अनुरोध छ।


विकास परियार
प्रमुख प्रशासकीय अधिकृत

सूची दर्ताका लागि आवश्यक कागजातहरू:


- कम्पनी/फर्म दर्ता प्रमाण पत्रको प्रतिलिपि।
- भ्याट/प्यान दर्ता प्रमाण पत्रको प्रतिलिपि।
- आ.व.२०८१/०८२ को कर चुक्ता प्रमाण पत्रको प्रतिलिपि। प्रशासकीय अधिकृत
- कम्पनी/फर्मको सेनेटरी प्याड सम्बन्धी स्पेशिफिकेशन प्रस्ताव
- सम्बन्धी निकायबाट अनुमति लिएको भए सोको प्रतिलिपि।

"व्यावसायिक र सिर्जनशील प्रशासन: विकास, समृद्धि र सुशासन"

<http://www.thasangmun.gov.np>, thasangmun@gmail.com, ९८५७६५०४९२, ९८५७६५०६६९



१४	Refresh rate up to 75Hz. 178° horizontal and vertical viewing angle. Screen can reduce blue light, protect eyes. Plastic body, ultra-narrow bezel, light weight and elegant. Shielding cover design, effectively preventing electromagnetic radiation. Stable structure design, highly durable. Automatically detect if the signal is connected successful. Support multiple language.	₹	पिस	
१५	8 Port Giga Switch: > Supports five 10/100 Mbps adaptive ports. > Small and light, it is easy to carry and has multiple chips embedded in it. > Easy to operate.	₹	पिस	
१६	Server Rack	₹	पिस	
१७	Splicing	₹	पिस	
१८	Installations Charge (जडान खर्च)	₹	जना	


 विकास परियार
 प्रमुख प्रशासकीय अधिकृत



सि. नं.	विवरण	परिमाण	इकाई	दर प्रति इकाई
१	Full Color HD Camera (8 MP): > 4K 1/1.8" CMOS image sensor, low luminance, and high definition image. > Outputs max. 4MP (2688x1520) @25/30 fps. > ROI, SVC, SMART H.264+/H.265+, AI H.264/H.265 > Rotation mode, WDR, 3D NR, HLC, BLC > Alarm: 2 in, 1 out; audio: 1 in, 1 out; supports max. 512 GB Micro SD card, built-in MIC. > IP67 and IK10 protection. > SMD 3.0.	१	पिस	
२	POE Giga Switch 6 Port: > Meets the requirements of IEEE802.3,IEEE802.3u,IEEE802.3x,IEEE802.3ab standards. > Meets the requirements of IEEE802.3af, IEEE802.3at, Hi-PoE power supply standards. > Manages PoE power consumption and PoE power on/off. Supports Intelligent PoE. > A wide operating temperature range and a full metal casing that is fully-enclosed and dust-proof.	१	पिस	
३	Media Converter : * Auto negotiation function allows UTP port to auto select 10M or 1000M and Full Duplex or Half Duplex. * UTP port supports MDI / MDI-X auto crossover * Supporting flow control * Internal circuit of prevented thunder could greatly reduce damage of the converter caused by thunderbolt induction. * Design of internal or external power supply for selection by users	१	पिस	
४	Metal Junction Box	१	पिस	
५	CAT 6 (Outdoor): > Power over Ethernet, compatible with one cable > Manufacturing excellence > Customized PVC outer sheath; meet CE CPR Eca flame retardant class certified	१	मी.	
६	RJ 45	१	मी.	
७	Power Socket	१	पिस	
८	Optical Fiber 6 F	१	पिस	
९	Service Wire	१	पिस	
१०	Patch Cable (3mtr)	१	पिस	
११	HDD 4 TB : Storage Capacity 4TB Form Factor 3.5 Inches Rotational Speed 5400 RPM Interface SATA Compatible Devices Desktops and CCTV/DVRs	१	पिस	
१२	Multi Plug Minimum 15 amp	१	पिस	
१३	NVR 8 Channel : > Max 80Mbps incoming bandwidth > Up to 1ch@8MP/4ch@1080P decoding 68 16CH AI NVR 1HDD DHI-NVR2116-4KS3 > H.265/H.264 codec decoding > Up to 8Mp resolution preview & playback > Supports 1HDD up to 16TB 43" Monitor (4K): Resolution is up to at 3840x2160.	१	पिस	

विकासीय अधिकृत
प्रमुख प्रशासकीय अधिकृत